

## Canning Shed/Facility Equipment Specifications

Item	Qty	Description
1	1 ea	<p><b>WALK IN COOLER</b></p> <p>Fast-Trak™ Indoor One Compartment Walk-In, 8' x 8' x 7'-7" H, compartments, cooler with smooth aluminum interior floor, 26 gauge embossed coated steel interior &amp; exterior finish, self-closing doors, locking deadbolt handle</p> <p>1 ea 15 year original equipment panel warranty</p> <p>1 ea Cooler compartment with floor</p> <p>1 ea Door size 26" x 78"</p> <p>1 ea lights</p> <p>1 ea Complete with condensor &amp; evaporator for the cooler</p>
2	3 ea	<p><b>WIRE SHELVING</b></p> <p>Packed 2 ea</p> <p>Shelf, 72" x 14", includes (4) sleeve clips per shelf, wire, epoxy coated, green, NSF.</p> <p>5 shelves &amp; (4) 74" posts per unit.</p>
3	7 ea	<p><b>RACK DOLLY</b></p> <p>Dishwasher Rack Dolly, 20-3/4"W x 20-3/4"D x 5-1/2"H, 6063-T5 aluminum construction, accommodates 19-3/4" x 19-3/4" dishwasher racks, 3" swivel casters, NSF</p>
4	3 ea	<p><b>WIRE SHELVING</b></p> <p>Packed 2 ea</p> <p>Shelf, 72"W x 18"D, includes: (4) sleeve clips per shelf, wire, chrome plated finish, NSF</p> <p>Qty &amp; size per drawing. 4 shelves with (4) 74" post per unit.</p>
5	1 ea	<p><b>RANGE, 24", 4 OPEN BURNERS</b></p> <p>Restaurant T Series Range, gas, 24", (4) 35,000 BTU open burners, cast iron grates, manual control, standard oven, (2) racks, stainless steel front, sides, ledge &amp; backguard with shelf, 6" chrome plated legs, 170,000 BTU, cETLus, ETL, CE</p> <p>1 ea Standard warranty: 1 year parts and labor</p> <p>1 ea Gas type to be determined</p>
6	1 ea	<p><b>TILTING SKILLET BRAISING PAN, COUNTERTOP, GAS</b></p> <p>Countertop Braising Pan/Stand, Gas, 16-gallon capacity, 8-3/4" deep stainless steel round pan with sloped sides &amp; pour lip, thermostatic control, stainless steel front &amp; sides, includes stainless steel stand with sliding drawer, 30,000 BTU (NOTE: LP Gas is NOT available)</p> <p>1 ea 1 year limited parts &amp; labor warranty, standard</p>

Item	Qty	Description
	1 ea	Natural gas (add -1 suffix) (specify elevation if over 2,000 ft.)
7	1 ea	<b>KETTLE, ELECTRIC, TILTING</b>  Tilting Kettle, Electric, 20-gallon true working capacity, 2/3 jacketed floor model, stainless steel splash proof console on right with faucet bracket, cleaning lock 1 ea 1 year limited parts & labor warranty, standard 1 ea NOTE: This unit includes: embossed gallon/liter markings, 316 stainless steel liner and heavy bar rim standard 1 ea 208v/50/60/3-ph, 12kW, 33.0 amps, direct wired, (20-gal kettle) standard
8	1 ea	<b>EXHAUST HOOD</b>  Exhaust Hood, Cartridge, size and shape per plan; with fan & fire suppression system
9	1 ea	<b>WORK TABLE, 63" - 72", STAINLESS STEEL TOP</b>  Work Table, 72"W x 30"D, 18/430 stainless steel top, with turndown edges on all sides, reinforced with channels, adjustable stainless steel undershelf, 1-5/8" dia. stainless steel legs, stainless steel over plastic adjustable bullet feet, NSF
10	1 ea	<b>REACH-IN UNDERCOUNTER REFRIGERATOR</b>  Undercounter Reach-In Refrigerator, one-section, self-contained refrigeration, 6.5 cu. ft. capacity, 33° to 45°F temperature range, (1) locking hinged self-closing door, (1) adjustable shelf, ventilated refrigeration, automatic evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, casters, rear mounted refrigeration, 260 watts, 115v/60/1-ph, 3.2 amps, 1/6 HP, cETLus, ETL, CE, ENERGY STAR® 1 ea 2 year labor & parts warranty, 5 years warranty on compressor 1 ea Contact factory for available options and accessories
11	1 ea	<b>BACK COUNTER, STRAIGHT</b>  Stainless steel back counter, with backsplash, straight line, closed base, with drawers size and shape per plan, edge and sound deadening as specified with locks
12	1 ea	<b>SECURITY UNIT</b>  Security Truck, heavy duty, 36"W x 18"D x 70"H, dolly base, 2" square grid mesh, lockable doors, 6" molded rubber swivel plate casters, (2) caster with brakes, corner bumpers included, chrome
13	1 ea	<b>WORK TABLE, 36" - 38", STAINLESS STEEL TOP</b>  Work Table, 36"W x 30"D, 18/430 stainless steel top, with turndown edges on all sides, reinforced with channels, adjustable galvanized undershelf, 1-5/8" dia. galvanized legs, adjustable high-impact corrosion-resistant feet, NSF

Item	Qty	Description
14	1 ea	<b>SHELVING, WALL-MOUNTED</b>  Economy Shelf, wall-mounted, 36"W x 12"D, 18/430 stainless steel, 1-1/2" rear turn up, (2) 8" angle supports, NSF
15	2 ea	<b>BLENDER, BAR</b>  Bar Blender, 44 oz. capacity, two speed motor, polycarbonate container, 2-piece lid, one-piece stainless steel blade, removable blade assembly, die-cast black zinc baked enamel base, 3/4 HP, NSF, cETLus  2 ea 2 year limited warranty, standard 2 ea 120v/50/60/1-ph, standard
16	1 ea	<b>WORK TABLE, 36" - 38", STAINLESS STEEL TOP</b>  Work Table, 36"W x 30"D, 18/430 stainless steel top, with turndown edges on all sides, reinforced with channels, adjustable stainless steel undershelf, 1-5/8" dia. stainless steel legs, stainless steel over plastic adjustable bullet feet, NSF
17	2 ea	<b>INDUCTION RANGE, COUNTERTOP</b>  Pro Countertop Induction Range, 14"W x 15-1/4"D x 3"H, G4 Engine, 4 IGBT switches, (100) power levels 80°-450° F (27°-232°C) range, 1-80 minute timer, knob control with digital readout, digital troubleshooting display, 14" maximum pan size, overheat protection, small-article detection, pan auto-detection function, empty-pan shut-off, stainless case top & aluminum bottom, rubber feet, 120v/60/1-ph, 6 ft cord with NEMA 5-15P, 1800W, 15amps, (2) year warranty, NSF, UL, FCC, imported, US model  2 ea 1 year parts & labor warranty
18	1 ea	<b>WORK TABLE, 40" - 48", STAINLESS STEEL TOP</b>  Work Table, 48"W x 30"D, 18/430 stainless steel top, with turndown edges on all sides, reinforced with channels, adjustable stainless steel undershelf, 1-5/8" dia. stainless steel legs, stainless steel over plastic adjustable bullet feet, NSF
19	1 ea	<b>SHELVING, WALL-MOUNTED</b>  Economy Shelf, wall-mounted, 36"W x 12"D, 18/430 stainless steel, 1-1/2" rear turn up, (2) 8" angle supports, NSF
20	2 ea	<b>FOOD PROCESSOR</b>  Combination Food Processor, 2.5 qt., clear polycarbonate cutter bowl, see thru lid, stainless steel "S" blade, on/off push buttons, direct drive, fan-cooled, 1725 RPM, 3/4 HP, 120v/60/1-ph, 7.0 amps, NEMA 5-15P, cETLus, ETL-Sanitation  2 ea 2 year parts & labor warranty
21	1 ea	<b>FOOD PACKAGING MACHINE</b>

Item	Qty	Description
		VacMaster® Vacuum Packaging/Sealer, 11-1/4" x 15-1/4" x 5" chamber, (1) 10-1/4" seal bar, dry rocker piston, includes (25) each of 6"x10", 8"x10", 10"x13" pouches, 110v/60/1-ph, 4.2 amps, 462w
22	1 ea	<b>SHELVING, WALL-MOUNTED</b>  Economy Shelf, wall-mounted, 72"W x 12"D, 18/430 stainless steel, 1-1/2" rear turn up, (3) 8" angle supports, NSF
23	1 ea	<b>OVERSHELF</b>  Economy Overshelf, wall mount with pot rack, 72"W x 12"D, 18/430 stainless steel, 1-1/2" rear turnup, (3) 8" angle supports, (7) stainless steel double prong hooks (BKSSDPH), NSF
25	1 ea	<b>LABELING MACHINE</b>  Control of the working cycle by micro-processor (PLC Siemens brand). Possibility of application of front & back labels; labelling unit designed for application of wrap-around labels on bottles and jars; printing unit for batch number or 'best-before' date.
26	1 ea	<b>GREASE TRAP</b>  Grease Trap, 40 lbs grease capacity, 20 gallons per minute, non-skid deck plate, removable baffles, no hub connections, includes T-Vent, 11 gauge carbon steel construction with corrosion resistant coating, PDI Certified, NYC compliant  1 ea 1 year warranty, standard
28	3 ea	<b>WALL / SPLASH MOUNT FAUCET</b>  OptiFlow™ Heavy Duty Faucet, splash mount, 8" O.C., 6" swing spout, double O-ring spout seal, 1/4 turn ceramic cartridges, polished nickel chrome finish, lead free, NSF, cCSAus  3 ea 2 year warranty, standard
29	2 ea	<b>POT RACK</b>  Next Generation Pot Rack, floating rack only, fits 24" shelf, (2) stainless steel double prong hooks (BKSSDPH), 2" 304 stainless steel flat bar (shelf not included)
30	1 ea	<b>HAND SINK</b>  Hand Sink, 14"W, wall mount, 10"Lx12"Dx5"H bowl size, 18 ga, 300 series stainless steel, 6" backsplash with 2" return, 1-1/2" drain, gooseneck faucet, strainer, Z-clip mounting bracket, NSF
31	1 ea	<b>MOP SINK</b>  Mop Sink, floor mount, 24-1/2"W x 19-3/8"D x 17"H, with 20" wide x 16" front-to-back x 12" deep bowl, (1) 3-1/2" heavy duty brass basket drain (BKDR-HD4), (1) 48" service faucet hose, (3) skirted sides, (1) service faucet with vacuum breaker, 5-slot utility tool holder & (6) plastic hooks, 18/304 stainless steel

Item	Qty	Description
	1 ea	2 year warranty, standard
32	1 ea	<b>WORK TABLE, WITH PREP SINK(S)</b>  Prep Table, with sink, 60"W x 30"D, 18/304 stainless steel construction, 16"wide x 20" front-to-back x 10" deep sink bowl on right, 6" backsplash, 4" O.C. deck mount lead-free faucet with 8" swing spout (BKD-8-G), includes basket drain, adjustable galvanized steel undershelf with cast aluminum corners, galvanized steel legs with metal over plastic adjustable bullet feet, NSF
33	1 ea	<b>DISHWASHER, UNDERCOUNTER</b>  (39716) Dishwasher, undercounter, door type, 23"W, 1080 dishes per hour, high temperature sanitizing, 3.0kW booster heater, 2.8kW tank heater, 14" dish clearance, thermal protection for wash & tank booster, rinsing thermo detector, 3-washing cycle, tank & boiler thermometer, proof rinse feature, double skinned door, includes: (1) peg rack, (1) flat rack, (1) cutlery tray, 304 stainless steel construction, 3/4 HP wash pump, CE, cETLus, TÜV  1 ea 1 Year parts & labor warranty, standard 1 ea 208-240v/60/1-ph, 16 amps, 3600 watts, standard
34	1 ea	<b>DISPOSER</b>  Disposer, complete with controls, vacuum breaker, solenoid valve & sink collar, basic unit only, 1 HP motor, stainless steel construction, includes mounting gasket  1 ea (1) year parts & labor warranty from date of installation (standard) 1 ea Voltage to be determined later
35	1 ea	<b>OVERSHELF</b>  Economy Overshelf, wall mount with pot rack, 36"W x 12"D, 18/430 stainless steel, 1-1/2" rear turnup, (2) 8" angle supports, (4) stainless steel double prong hooks (BKSSDPH), NSF