









# Equipment Specifications

## Commercial Kitchen

Item #	Qty.	Description
1	1 ea	<p><b>WALK-IN COOLER/FREEZER, COMBO</b></p> <p>Walk in combination box size 13'-3" x 7'- 3" x 7' 6" tall See attached floor plan for layout (1) cooler , (1) freezer, Led 4' cooler / freezer light fixture, no floor in cooler, NSF floor 22 gauge stainless steel interior floor for freezer, vinyl screed, stucco embossed galvalume 26 gauge exterior, stucco embossed galvalume 26 gauge interior NSF approved (2) 34" x 78" doors</p> <p>Cooler refrigeration Non-charged preassembled med temp R system 1/2hp 1 phase 208/230 volt with hermetic compressor, outdoor weather hood, crank case heater start kit, sight glass, evaporator coil medium temp 115v , high/low pressure control, receiver, site glass/ moisture indicator, head pressure control valve, expansion valve and solenoid valve,</p> <p>Freezer refrigeration - Non- charged preassembled low temp r system, 1-1/2 hp 208/230v with hermetic compressor, outdoor weather hood, crankcase heater, start kit, high/low pressure control, receiver, site glass / moisture indicator, pressure control valve, electric defrost timer,, evaporator, expansion valve, and solenoid valve and drain line heater -10 degree</p>
2	8 ea	<p><b>WIRE SHELVING</b></p> <p>Packed 2ea</p> <p>Shelf, 42" x 18", wire, epoxy coat finish, NSF</p>
	8 ea	Post, 72"H, epoxy coated (priced per each)
	12 ea	Shelf, 60" x 18", wire, epoxy coat finish, NSF
	12 ea	Post, 72"H, epoxy coated (priced per each)
	4 ea	Shelf, 36" x 18", wire, epoxy coat finish, NSF
	4 ea	Post, 72"H, epoxy coated (priced per each)
	16 ea	<p><b>WIRE SHELVING</b></p> <p>Packed 2 ea</p> <p>Shelf, 42"W x 18"D, wire, chrome plated finish, NSF</p>
	16 ea	Shelf Post, 72"H, chrome plated (priced per each)
3	2 ea	<p><b>SECURITY UNIT</b></p> <p>Security Shelving Unit, wire, 24"D x 24"W x 66"H, 2" square grid mesh, top &amp; bottom shelves, lockable double door, adjustable levelers, chrome</p>

Item #	Qty.	Description
4	1 ea	<b>3-COMPARTMENT SINK</b>
		<p>Custom 3- compartment sink with. Sink bowls to be heavy gauge type 304 stainless steel deep drawn, seamless with all corners coved. Top - including backsplash with closed back and drainboards in heavy gauge 430 stainless steel. Drainboards to be "V" crease for positive draining. 9-1/2" high backsplash,. Legs to be 1-5/8" O.D stainless steel with adjustable bullet feet. Sink bowls 20" x 16" x 13.5" deep. Size: 80" long by 27" wide. See floor plan for layout.</p>
	1 ea	With Complete with splash mount faucet, Strainer Twist and Lever Waste.
5	1 ea	<b>SHELVING, WALL-MOUNTED</b>
		
		Premium Shelf, wall-mounted, 60"W x 12"D, 18/304 stainless steel, 1- 1/2" rear turn up, (2) 8" angle supports, NSF
6	1 ea	<b>WORK TABLE</b>
		
		Work Table, 36"W x 30"D, 18/430 stainless steel top, with turndown edges on front & sides, reinforced with channels, 5" backsplash, adjustable stainless steel undershelf, 1-5/8" dia. stainless steel legs, stainless steel over plastic adjustable bullet feet, NSF
7	1 ea	<b>GREASE TRAP</b>
		
		Grease Interceptor, with drawoff, 40 lb. capacity, semi-automatic, (20) gallons per minute rate flow, includes: drawoff hose, shut-off valve, epoxy coated steel
8	1 ea	<b>SOILED DISHTABLE</b>
		
		Soiled Dishtable, straight design, 26"W x 30-7/8"D x 46-1/4"H, right-to- left operation, 18/304 stainless steel top, 10"H backsplash, 20" x 20" x 8" deep pre-rinse sink, 8" O.C. splash mount faucet holes, raised rolled edges on front & side, 3-1/2" basket drain included, galvanized steel legs & side bracing, adjustable high impact corrosion resistant feet, NSF

Item #	Qty.	Description
9	1 ea	<b>DISPOSER W/PRE-RINSE SPRAY UNIT</b>
		 <p>SS-150™ Complete Disposer Package, with 12" diameter bowl, 6-5/8" diameter inlet, with removable splash baffle &amp; reversible bowl cover, 1-1/2 HP motor, stainless steel construction, includes syphon breaker, solenoid valve, flow control valve, manual reverse switch, adjustable leg kit</p>
	1 ea	(1) year parts & labor warranty from date of installation (standard)
	1 ea	Standard height disposer body
	1 ea	Voltage to be determined later
	1 ea	Syphon breaker standard, 1/2" (11477)
	1 ea	W/(1) Pre-Rinse w/Wall Bracket.
10	1 ea	<b>DISHTABLE SORTING SHELF</b>
		 <p>Slant Rack Drying Shelf, wall mount, 42"W x 22"D, 18/304 stainless steel top, rolled front edge, weep accepts 1" nylon tubing (nylon tubing not included), mounting brackets included, NSF</p>
11	1 ea	<b>DISHWASHER, DOOR TYPE</b>
		 <p>Dishwasher, door type, 26"W, straight or corner design, high temperature sanitizing, 7.5kW booster heater, 6.0kW tank heater, 15.7" door clearance, thermal protection for wash &amp; tank booster, rinsing thermo detector, 3-washing cycle, tank &amp; boiler thermometer, proof rinse feature, 304 stainless steel construction, 1-1/2 HP wash pump, 8200 watts, 46.0 amps, 208-240v/60/1-ph, CE, cETLus, TÜV</p>
12	1 ea	<b>CLEAN DISHTABLE</b>
		 <p>Clean Dishtable, straight design, 26"W x 30-7/8"D x 46-1/4"H, right-to- left operation, 18/304 stainless steel top, 10"H backsplash, raised rolled edge on front &amp; side, galvanized steel legs &amp; side bracing, adjustable high-impact corrosion-resistant feet, NSF</p>
13	1 ea	<b>EXHAUST HOOD W/FIRE SYSTEM AND GAS VALVE</b>
		<p>Exhaust hood - Wall canopy hood with front perforated supply plenum with built-in 3" standoff, 430 s/s were exposed, complete with stainless steel filters 20" x 16", canopy lights, exhaust riser, closure panels to ceiling with matching s/s. Hood dimensions are 9'-0" long X 60" deep. Closure panels dimensioned to 9' - 0" minimum finished Ceiling height. Total CFM 2035. Total Supply CFM 1620 Electrical Package installed in utility cabinet at Factory. Fire Suppression System provided w/pre-pipe @ Factory w/Detection. Fans by mechanical contractor.</p>

Item #	Qty.	Description
14	1 ea	<b>FRYER</b> Heavy Duty Fryer, gas, floor model, 40 lb. capacity, (3) burners, standby pilots, 200°F- 400°F temperature range, self-reset high temperature limiting device, oil cooling zone seated in the bottom of the tank, stainless steel structure, adjustable stainless steel legs, 102,000 BTU, cETLus, ETL
	1 ea	1 year warranty
	1 ea	Natural gas, Gas hose and regulator
15	1 ea	<b>COMBI OVEN</b> SelfCooking Center® Combi Oven/Steamer, electric, (6) 18" x 26" full size sheet or (12) 12" x 20" full size hotel pan capacity, iCookingControl with 7 modes, HiDensityControl®, iLevelControl, Efficient CareControl, Combi-Steamer with 3 modes, core temp probe with 6 point measurement, hand shower with automatic retracting system, (3) grid shelves, ethernet interface, 208v/60/3-ph, 61.4 amps, 22.1 kW (dual voltage: retrofitable to 240v/60/3-ph, 70.8 amps, 22.1 kW) ENERGY STAR®
	1 ea	2 years parts and labor warranty
	1 ea	Door hinged on right std.
	1 ea	With Water Filter, C&P, Gas Hose and Regulator
	1 ea	
15B	1 ea	<b>EQUIPMENT STAND FOR COMBI OVEN</b> 18/430 stainless steel, Legs to be 1-5/8" O.D stainless steel with adjustable bullet feet, NSF
16	1 ea	<b>RANGE, 36", 6 OPEN BURNERS</b> Heavy Duty Restaurant Range, gas, 36", (6) 32,000 BTU open burners, 26-1/2" standard oven, includes (1) rack, stainless steel front, sides & high shelf, 6" chrome plated legs, 67.0 kW, 227,000 BTU, ETL-Sanitation, NSF
	1 ea	Standard one year limited warranty on parts & labor
	1 ea	Natural Gas
	1 ea	26-1/2" Standard oven
	1 ea	With Gas Hose, Regulator and Casters w/ Break
17	1 ea	<b>SANDWICH / SALAD PREPARATION REFRIGERATOR</b> Sandwich/Salad Top Reach-In Refrigerator, two-section, self-contained refrigeration, 12.0 cu. ft. capacity, includes (12) 1/6 stainless steel pans, 33° to 45°F temperature range, (2) locking hinged self-closing doors, (2) adjustable shelves, poly cutting board, ventilated refrigeration, automatic lighting & evaporation, air defrost, stainless steel interior & exterior, galvanized steel back, casters, front breathing side mounted refrigeration, 560 watts, 115v/60/1-ph, 6.5 amps, 1/3 HP, cETLus, ETL, CE
	1 ea	2 year labor & parts warranty, 5 years warranty on compressor

Item #	Qty.	Description
18	2 ea	<b>BAR BLENDER</b> Blending Station® Advance®, high-impact, on-counter, 48 oz. (1.4 liter) capacity, (93) speeds, variable speed control, electronic touch pad controls, stackable, Advance® container, removable compact cover, (34) programs, automatic shut-off, includes: blade assembly & lid, clear, 3-peak HP, RoHS compliant, cULus, CE, NSF
	2 ea	3 years warranty on motor base parts & 1 year warranty on labor, standard
	2 ea	120v/50-60/1-ph, 15 amps, standard
19	1 ea	<b>DROP-IN SINK</b> Drop-In Sink, one compartment, 12-1/4"W x 18"D O.A., 20/304 stainless steel construction, 10" wide x 14" front-to-back x 9" deep bowl, 4" O.C. deck mount faucet , 3-1/2" drain opening, includes basket drain with crumb cup, 11-1/8" x 17" cutout required, NSF
	1 ea	
20	1 ea	<b>SODA ICE &amp; BEVERAGE DISPENSER</b>
	1 ea	For custom configurations of SV units, alternate voltage and side splash guards,
	1 ea	120v/60/1-ph, 2.8 amps, standard
	1 ea	2 year limited parts & 1 year limited labor warranty (USA)
21	1 ea	<b>REFRIGERATED MERCHANDISER</b> Refrigerator Merchandiser, two-section, self-contained refrigeration, 47.1 cu. ft. capacity, 33° to 45°F temperature range, (2) locking hinged glass doors, (8) adjustable shelves, ventilated refrigeration, LED interior lighting, automatic evaporation, digital temperature control, air defrost, stainless steel interior & exterior, galvanized steel back, bottom mounted
	1 ea	refrigeration, 400 watts, 115v/60/1-ph, 4.3 amps, 1/3 HP, cETLus, ETL, CE, ENERGY STAR®
		2 year labor & parts warranty, 5 years warranty on compressor
22	1 ea	<b>COFFEE BREWER</b> TWIN-APS Airpot Coffee Brewer, automatic, brews 15 gallons per hour capacity, hot water faucet, digital timer, pourover features, two brew heads, SplashGard® stainless steel funnels, brews into (2) 1.9 to 3 liter airpots (sold separately), stainless decor, 120/240v/60/1-ph, 6250 watts, 26 amps, 20-90 psi, 1/4" male NPT, UL, NSF
	2 ea	Airpot, 2.5 liter (84 oz.), push-button, glass insulation, chrome finish with black trim, 1-pack, ETL

Item #	Qty.	Description
23	1 ea	<b>TEA BREWER</b> Twin Iced Tea Brewer, (2) 3-gallon capacity, 26.7 gallon/hour, rotating brew basket, base platform adapter, dedicated dilution nozzles, brew selection switch, adjustable sleep time, SplashGard® funnel, Quickbrew system, color coded decals, designed for brewing into (2) 3.5 gallon BUNN narrow tea dispensers (sold separately), 120v/60/1- ph, 1730w, 14.4amps, NEMA 5-15P, cord attached, UL, NSF
	1 ea	Narrow Iced Beverage Dispenser, 3.5 gallon capacity, sump dispense valve, front-back handles, 8" cup clearance, for use with BUNN TB-3, TB -3Q and ITCB brewers with 29" trunk height, NSF
24	1 ea	<b>MEAT SLICER</b> Meat Slicer, manual, 10" diameter knife, angle/gravity feed, light duty, top-mounted metal sharpener with (2) grinding stones, belt driven, stainless steel blade, removable ball bearing carriage, permanently attached ring guard, anodized aluminum, non-slip rubber feet, 110v/60/1-ph, 1/4 HP, NEMA 5-15P, ETL, cETLus
	1 ea	1 year limited warranty
25	2 ea	<b>HAND SINK W/EYE WASH, SOAP &amp; TOWEL DISPENSER</b> Space Saver Hand Sink, wall mount, 9" wide x 9" front-to-back bowl, 4" O.C. deck mount faucet holes, NSF With faucet, eyewash, 1-7/8" drain opening, basket drain & mounting bracket
26	3 ea	<b>Double Stacked Lockers</b> Row of three (3) double stacked combination lock lockers with sloped top and closed bottom. Combination locks with keyed emergency access and combination change

